

Roland DGA GuardLam™ Gloss Floor Overlaminates Film: ESM-GLGF

Product Overview

Roland DGA GuardLam Gloss Floor Overlaminates Film is UL-410 certified for floor applications. This 4-mil gloss calendared overlaminates is also optically clear and can be used for window applications, along with other signage applications.

Specifications

Film Caliper: 4 mil
Finish: Gloss
Basis Weight: 0.30 msi
Adhesive: Acrylic
Liner: Clear Film

Liner Caliper: 2 mil
Core Diameter: 3"
Outdoor Durability: 3 years
Shelf Life: 1 year
Available Size: 20", 30", and 54" x 150'

Applications

Floor Graphics
Window Graphics
Partial Vehicle Wraps

Decals
POP Displays
Indoor/Outdoor Signage

Part Number

ESM-GLGF-150-20
ESM-GLGF-150-30
ESM-GLGF-150-54

Storage Conditions

ESM-GLGF Roland DGA GuardLam Overlaminates Film should be handled with care to prevent surface contamination that may affect the printable surface of the product. This material should be processed and stored in an environment of 65° - 85° F (18° - 29° C) and 30 - 50% relative humidity (non-condensing) that is clean and relatively dust-free. We recommend storing this product in its original packaging in a cool, dry area until ready for use. If storage conditions are outside the recommended operating ranges, allow the material to acclimate to the production environment for at least 24 to 48 hours before use.

Roland Certified Media Guarantee

This product is sold for the usage of the applications stated in this document. The product is free of defects when applied to printed calendared media. It is not compatible with cast vinyl.