



NatureWalk

Recyclable polyester textile backed with repositionable, removable adhesive.

Dimensionally stable and tear resistant, NatureWalk is an ideal environmental choice for a wide variety of applications.

The naturally non-skid face film is a great one-step solution for floor graphics or any project where a textured film is desired.

APPLICATIONS

- Wall and Door Murals
- Museum Exhibits
- Floor Graphics
- Trade Shows

NatureWalk

MATERIAL

Face Film	Specially Coated Woven Polyester
Back Side	Grey Back for Increased Opacity
Adhesive	Removable Solvent Acrylic (80µ +/- 5µ)
Liner	Siliconized Paper
Film Thickness	7 mil (180µ +/-5µ)
FR Certification	Testing In Progress, M1, B1
Slip Resistance	ANSI A137.1/A326.3, R10

DURABILITY

Interior	Vertical Surfaces - Up to 1 year Flooring Surfaces - Up to 6 Months, Dependent on Traffic
Environment	Humidity & Solvent Resistance - Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 75°F (+ 15°C to +24°C) and Relative Humidity Between 40% and 65%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (+10°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removal Temp	+50°F (+10°C) or Greater

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean installation surface with a mild detergent and water and dry thoroughly. ALWAYS clean and dry glass surface prior to application.

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Digital - Solvent, Eco-Solvent, Latex & UV Inks
- Screen Print



Material Sizes

- 54" x 100'



Advantages

- Leaves No or Almost No Adhesive Residue
- Polyester Film Is Recyclable Where Allowed
- Easy To Apply and Remove
- Print and Go - No Lamination Needed!

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

1-704-872-2216 • www.cgxusa.com



www.cgxusa.com

CONTINENTAL
GRAFIX