# ${\sf Interlam}^{^{\sf m}}$

## Pro Emerytex®

Interlam™ Pro Emerytex® is a 4 mil (100µ) monomeric soft calendared PVC laminating film with a matte pebble textured finish, coated on one side with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. Interlam™ Pro Emerytex® has been tested according to the EN 13036-4 test method and awarded a rating of low slip potential.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN HIGH TRAFFIC INDOOR AND OUTDOOR DISPLAY AREAS
- PROVIDES UV PROTECTION FOR OUTDOOR GRAPHICS
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF -RESISTANT FINISH IS REQUIRED
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC<sup>TM</sup> PRINT MEDIA TO CREATE A SLIP-RESISTANT FLOOR GRAPHIC FOR LOW TO MID-TRAFFIC AREAS (UP TO 6 MONTHS)

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

### **TECHNICAL SPECIFICATION**

#### PRODUCT STRUCTURE

**Film** Matte Pebble Textured Monomeric Soft Calendared PVC

**Adhesive** Acrylic (Pressure Sensitive)

**Release Liner** 2 Side PE Coated, 1 Side Siliconized Kraft

#### PRODUCT CHARACTERISTIC

 Film Thickness
 4 mil (75μ)
 5 mil

 Adhesive Layer
 1 mil (25μ)
 (125μ)

Film/Adhesive Ratio 4:1

**UV Protection Factor**Film contains UV stabilizers, which prevent film degradation and provide UV protection to the

underlying image

Outdoor Durability 3 Years

**Application Temperature** >41°F (20°C)

Service Temperature Range -13°F to 302°F (-25°C to 150°C)

Fire Rating Class 0

**FDA Approved** 21 CFR 177.1975

Peel Strength (20 min, FTM1) 11 N/25mm

**Shelf Life** 1 year

Storage Conditions 59°F to 72°F (15°C to 22°C);

50 - 55% Relative Humidity

#### PROCESS SETTINGS

**Equipment Type & Temperature** 

Speed

Roller Laminator Room temperature to 104°F (40°C) 1 ft to 8 ft (0.3m to 2.5m) per minute

Press Not recommended





9240 Manchester Road St. Louis, MO 63144 dpg.schillers.com 314-968-3650 • 800-366-7244