

ReTac[®]

Smooth 150

Our 6 mil (150 μ), white polymeric printable PVC film with ReTac[®] ultra removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.


Dimensionally stable, ReTac[®] Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. And, with ReTac[®] on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed.

ReTac[®] Smooth 150 has a Class 0 Fire Rating for surface spread of flame.

- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

6 mil White Phthalate-Free Polymeric PVC  Matte

 (Eco) Solvent Latex UV

 ReTac[®] ultra removable and re-positionable adhesive

 Widths up to 54 in

 **5** YEARS DURABILITY **INTERIOR AND EXTERIOR**
(2 YEAR REMOVABILITY EXTERIOR)

EASY APPLICATION AND REMOVAL



APPLICATIONS

- Smooth Flat Surfaces
- Point Of Sale Graphics
- Interior Décor
- Decals & Stickers

Certified for
HP Latex Inks

DRYTAC[®]
ADHESIVE SCIENCE

www.drytac.com

ReTac[®]

Smooth 150

ReTac[®] Smooth 150 is a 6 mil (150µ) printable white, phthalate-free polymeric PVC film, coated on one side with ReTac[®] ultra removable adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac[®] Smooth 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- RETAC[®] IS A PHTHALATE-FREE FILM.
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUES AND WALL MURALS.
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, GLASS, AND LOW SURFACE ENERGY SUBSTRATES.
- RETAC[®] SMOOTH 150 HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	ReTac [®] ultra removable and re-positionable adhesive technology
Release Liner	135 gsm 1 side siliconized clay coated Kraft paper

PRODUCT CHARACTERISTIC

Film Thickness	6 mil (150µ)	6.9 mil (172µ)
Adhesive Layer	0.9 mil (22µ)	
Film/Adhesive Ratio	6:0.9	
UV Protection Factor	Not Applicable	
Outdoor Durability	5 year; 2 years removability	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Flame Retardancy	Class 0 BS 476 - Part 6 & 7 Fire Rating	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

OVERLAMINATE RECOMMENDATIONS

When using ReTac[®] Smooth 150, an overlaminate can be used for maximum life expectancy. Products recommended for use with ReTac[®] Smooth 150 are Drytac's Interlam™ Pro overlaminates.

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com