



## WALL GRAPHICS®

### SPMWGW

4.0 mil. Wall Graphics Vinyl

*With an Ultra Removable Adhesive and a 90# Release Liner*

Catalina Graphic Films' Mojave Digital Media for Wall Graphics are ideal for with Eco-Solvent, Solvent, UV-Based, and Latex inkjet printers. These films are also available for Screen Printing, and can be top-coated for improved ink adhesion for printing methods such as Offset, Litho, Flexographic and UV printing.

RECOMMENDED APPLICATIONS
<ul style="list-style-type: none"> <li>• Decals</li> <li>• Indoor</li> </ul>

OVERVIEW	
Face Film	3.5 ± 0.2 mils flexible vinyl
Adhesive	W21 clear acrylic pressure activated ultra removable adhesive
Liner	90# (6.5 ± 0.2 mils) white polyethylene coated two side-silicone coated one side paper. The back side on the release liner has a special matte coating on it for digital applications.
Opacity	Good
Gloss Level	Matte
Indoor Durability	2 Years

SPECIFICATIONS	
Application	<p>This product is intended for use in the production of high quality interior graphics requiring easy and clean removal from flat, painted wall surfaces (non textured walls only), most types of wallpaper and wood paneling.</p> <ul style="list-style-type: none"> <li>• Not to be applied to unfinished walls. Has to be applied dry to dry (not wet) walls</li> <li>• Not recommended to use an overlaminate with an oversized Wall Graphic</li> <li>• Individual graphic panels not to exceed 60" x 84"</li> <li>• Panels need to have "portrait" orientation as opposed to "landscape"</li> </ul>
Print Methods	Solvent or UV curable screen printing inks, solvent or eco-solvent and latex inks.
Total Product Thickness	11.0 - 12.0 mils
Minimum Application Temperature	+40° F.
Service Temperature Range	-10° F To +140° F.
Expected Lifetime Exterior	This film is <b>not</b> recommended for outdoor use
Adhesion	5 ± 2 oz/in (180° adhesion from SS, 20 minute room temperature dwell)
Water Resistance	Good
Chemical Resistance	Good resistance to most wall cleaning/household cleaning products
Shelf Life	One year when stored under conditions of 70°F and 50% relative humidity.
Available Colors	matte white

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

To order or request product samples,  
contact your local authorized dealer or call direct

Customer Service **800-333-3136** or visit our websites:



27001 Agoura Road Suite 100  
Calabasas Hills California 91301  
Phone: (818) 880-8060  
Fax: (818) 880-1144  
Atlanta Sales: (800) 922-5880  
Chicago Sales: (800) 766-4939  
E-mail: [info@catalinagraphicfilms.com](mailto:info@catalinagraphicfilms.com)

