

SOLVENT BACKLIT 200 MATTE

(SO600)


Details

- Wide color gamut, and vivid colors with or without light.
- Translucent polyester coated backlit film designed for top quality backlit applications.
- Strong and rigid base polyester material, and semi-matte surface
- Work with all the popular solvent, Latex and UV curable inkjet printers.
- Fast drying time, and Anti-slip treatment
- Available longer lengths at 164 ft & 300 ft, wide widths up to 72", 80" & 87"

- HP LATEX Profiled

Profiled Only

Specifications

Length (ft)	100	Width (inch)	50"/54"/60"/72"/80"/87"
Weight (gsm)	275	Coating	Resin
Caliper (mil)	8.2	Base Material	PET
Inner Core (inch)	3	Printer	
Surface	Matte		

KEY FEATURES

- Wide color gamut, and vivid color with light
- Outstanding color expression
- Strong and rigid base material at 7 mil PET
- Up to 87"
- Anti-slip treatment

Application

- Lightbox Graphic, Backlit Trade Show Display, Department Store Display, Luminous Advertising Surface, Bus Shelter & Metro Illuminated Signage

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

www.naturamedia.us

1505 Pavilion Place Suite D, Norcross GA 30093

TEL 470-359-2111

FAX 470-359-2199