



ELECTRICALLY CHARGED
POLYPROPYLENE

NEKOOSA.COM



ClingZ[®] is an adhesive free, electrically charged graphic film that adheres to any dry interior surface, and is easy to reposition.

Effortless to apply and fine-tune into position, ClingZ[®] will not damage even the most sensitive surfaces or leave a trace of residue. ClingZ uses an electric charge which means no glue, tape, tacks, or pins required. ClingZ is ideal for temporary indoor signage and marketing applications.

ClingZ[®] Offset

ClingZ[®] Standard[†]

This offset printable product is suitable for a job of any size and ideal for temporary indoor marketing applications for up to 6 months. The product consists of a polypropylene face and a 10 pt. printable backer.

ClingZ[®] Versaliner Offset*

Designed for offset and UV inkjet flatbed printing, ClingZ Versaliner uses a full-contact backer for improved handling on press. This product consists of a polypropylene face and a 10 pt. printable backer. Use ClingZ Versaliner if prints need extra finishing like die and kiss cutting.

ClingZ[®] HP Indigo

Optimized for excellent compatibility with HP Indigo printers, ClingZ for HP Indigo combines the same unique features of ClingZ Versaliner with all the advantages of digital printing. This product consists of a polypropylene face and a 10 pt. printable backer.

ClingZ[®] UV Wide Format[†]

Produced in rolls, with a full contact layflat backer, ClingZ UV Wide Format enables designers to use the ClingZ technology for even more applications. This product consists of a polypropylene face and a 3 mil. PET backer.

Applications

- Screen Safe Labels
- In-Store Promotional Signage
- Large Format Graphics
- Tileable Murals
- Point-of-Purchase Signage
- Reverse Sided Graphics
- Trade Show & Event Signage
- Window Graphics
- Holiday Décor & Decals
- Guerrilla Marketing
- Dry Erasable Posters[†]

Product Information

- Adhesive-free media for any dry interior surface
- Effortless to apply and remove, repositionable – no surface damage
- Chemically inert, PVC-free, phthalate-free, and recyclable
- Can be die cut, kiss cut, perforated, scored, and folded
- Ability to easily tile large graphics
- Compatible with conventional and UV offset, HP Indigo, and UV wide format

Colors Available

- White
- Clear





ELECTRICALLY CHARGED
POLYPROPYLENE

NEKOOSA.COM



TECHNICAL DATA ▶

Physical Properties		Thickness Type	Printer Compatibility	Measurement
Color	White and Clear	Film Thickness	Offset, Versaliner	2 mil / 50.8 μ
Film Material	Polypropylene		HP Indigo, UV Wide Format	2 mil / 50.8 μ
Min App Temperature	32° F / 0° C	Backer Type	Offset, Versaliner, HP Indigo	10 pt paper
Service Temperature	-0° to 105° F / -18° to 65° C		UV Wide Format	PET
Recyclability Category	Plastics #5	Backer Thickness	Offset, Versaliner, HP Indigo	10 mil / 254 μ
Shelf Life	1 Year		UV Wide Format	3 mil / 76.2 μ
Outdoor Durability	None	Overall Thickness (Film + Liner)	Offset, Versaliner	12 mil / 304.8 μ
			HP Indigo	12 mil / 304.8 μ
		Overall Thickness	UV Wide Format	5 mil / 127 μ

		Clear					White				
Printer Compatibility	Product	Size	GSM	M Wgt	Sheets/Carton	Sheets/Skid	GSM	M Wgt	Sheets/Carton	Sheets/Skid	
Offset (Conventional & UV Wide Format)	ClingZ® Standard Offset	19"x25"	243	164 lb	200	2,000	240	162 lb	200	2,000	
		23"x35"		278 lb	200	2,000		275 lb	200	2,000	
		28"x40"		387 lb	200	2,000		382 lb	200	2,000	
	ClingZ® Versaliner Offset*	20"x28"	246	196 lb	250	2,000	243	193 lb	250	2,000	
28"x40"		392 lb		250	2,000	387 lb		250	2,000		
HP Indigo	ClingZ® for HP Indigo	12"x18"	261	80 lb	500	—	269	82 lb	500	—	
		13"x19"		92 lb	500	—		95 lb	500	—	
		20.5"x29.5"		225 lb	300	1,200		231 lb	300	1,200	
UV Wide Format	ClingZ® UV Wide Format	42"x150'	155	17 lb	1 roll/carton		161	17 lb	1 roll/carton		
		54"x150'		21 lb	1 roll/carton			22 lb	1 roll/carton		

*Also available upon request ClingZ® Versaliner for flatbed printers.

Certified for
HP Indigo

HP CERTIFIED:
ClingZ for HP Indigo Clear 7500, 5000, 5500, 5600 multi-shot, 7000, 7600, 7800, and 7900
ClingZ for HP Indigo White 7000, 5000, 5500, 5600 multi-shot, 7500, 7600, 7800, and 7900

