



## WALL GRAPHICS®

### SPMWG6

6.0 mil. Wall Graphics Vinyl

*With an Ultra Removable Adhesive and a 90# Release Liner*

Catalina Graphic Films' Mojave Digital Media for Wall Graphics are ideal for with Eco-Solvent, Solvent, UV-Based, and Latex inkjet printers. These films are also available for Screen Printing, and can be top-coated for improved ink adhesion for printing methods such as Offset, Litho, Flexographic and UV printing.

#### RECOMMENDED APPLICATIONS

- Decals
- Indoor

#### OVERVIEW

<b>Face Film</b>	6.0 ± 0.2 mils flexible vinyl
<b>Adhesive</b>	W79 clear acrylic pressure activated ultra removable adhesive
<b>Liner</b>	90# (6.5 ± 0.2 mils) white polyethylene coated two side-silicone coated one side paper. The back side on the release liner has a special matte coating on it for digital applications.
<b>Opacity</b>	Good
<b>Gloss Level</b>	Matte
<b>Indoor Durability</b>	2 Years

#### SPECIFICATIONS

<b>Application</b>	<p>This product is intended for use in the production of high quality interior graphics requiring easy and clean removal from flat, painted wall surfaces (non textured walls only), most types of wallpaper and wood paneling.</p> <ul style="list-style-type: none"> <li>• Not to be applied to unfinished walls. Has to be applied dry to dry (not wet) walls</li> <li>• Not recommended to use an overlamine with an oversized Wall Graphic</li> <li>• Individual graphic panels not to exceed 60" x 84"</li> <li>• Panels need to have "portrait" orientation as opposed to "landscape"</li> </ul>
<b>Print Methods</b>	Solvent or UV curable screen printing inks, solvent or eco-solvent and latex inks.
<b>Total Product Thickness</b>	13.0-14.0 mils
<b>Minimum Application Temperature</b>	+40° F.
<b>Service Temperature Range</b>	-10° F To +140° F.
<b>Adhesion</b>	11 ± 2 oz/in (180° adhesion from SS, 20 minute room temperature dwell)
<b>Water Resistance</b>	Good
<b>Chemical Resistance</b>	Good resistance to most wall cleaning/household cleaning products
<b>Shelf Life</b>	One year when stored under conditions of 70°F and 50% relative humidity.
<b>Available Colors</b>	matte white

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



27001 Agoura Road  
Suite 100  
Calabasas Hills  
California 91301

Phone: (818) 880-8060  
Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880  
Chicago Sales: (800) 766-4939

E-mail: [info@catalinagraphics.com](mailto:info@catalinagraphics.com)

To order or request product samples,  
contact your local authorized dealer or call direct

Customer Service **800-333-3136** or visit our websites:

