



PolySOL™ Roll-Up Film 7 mil

■ satin 3515

PRODUCT DESCRIPTION

3515 PolySOL™ Roll-Up is a 7 mil polyester display film with a “low glare” satin finish and an instant dry, water resistant coating. The durable 7 mil construction is intended to be used unlaminated to create a retractable banner. It can also be overlaminated to create a durable tradeshow panel engineered to withstand repeated rolling in portable display units without cupping, warping or scratching. For additional protection 3515 can be overlaminated with both pressure sensitive and hot laminates.

Physical Properties

Caliper	7 mil
Basis Weight	240 g/m ²
Gloss (60°)	16
Opacity	> 99%

*All values listed are target values

Advantages

- Stiff Polyester Base
- Low Glare Satin Finish
- >99% Opacity / Blockout
- Instant Dry / Water Resistant
- Lay Flat / Will Not “Cup” Over Time

Applications

- Durable Tear Resistant Roll-Ups where Blockout is Needed
- Traveling Seminars, Recruitment Sessions, Training Events

List of printers



Printer	Ink
Epson® GS 6000	Eco-Solvent I
Hewlett Packard® DJ 8000s, 9000s, 10000s	Low-Solvent
HP® L25500, L26500, L28500, 300 Series	Latex
Hewlett Packard H35000, H45000	788 UV pigment inks
Mimaki® JV3, JV33, JV 5	ES, SS2, SS2-1, HS
Mimaki® UVJ / UJV 160	UV Curable
Mutoh® ValueJet	Eco-Solvent
Roland® VP, SP, XC, XJ, SJ / AJ	ECO-SOL MAX / Eco-Xtreme
Océ Arizona 250 GT, 200GT	UV Inks
FujiFilm Acuity HD 2504	UV Inks
Vutek PV, QS, DS Series	UV Ink

*For further information please refer to our website www.sihlinc.com

Certified for
HP Latex Inks

How to Buy

For additional Sihl Digital Imaging product information, please call 1-800-366-7393 or visit our website www.sihlinc.com where you can also find an authorized Sihl reseller near you.