



SyntiSOL™ PP Film with EasyTack™

■ satin 3529

PRODUCT DESCRIPTION

3529 SyntiSOL™ is a tear resistant, smooth polypropylene display film with a “low glare” satin, water resistant, scratch resistant coating and a proprietary low tack self-adhesive. The special low-tack glue allows for easy, 100% bubble-free application and residue-free removal on glass and other flat surfaces. The SyntiSOL™ family of products lay extremely flat, both on the printer and in final application. 3529 is compatible with solvent and UVC.

Advantages

- EasyTack - Proprietary Removable Adhesive
- Tear Resistant Polypropylene Base
- Kiss-Cut Liner
- Water & Scratch Resistant
- Fast Drytime
- Alternative to Scrim Banner and PSA Vinyl

Applications

- Print and Contour cut for Window or Wall Graphics
- “Fathead” type graphics

Physical Properties

Caliper	13 mil (8 mil polypro / 5 mil liner)
Basis Weight	220 g/m ²
Gloss (60°)	15
Opacity	> 96%

*All values listed are target values

List of printers



Printer	Ink
Epson® GS 6000	Eco-Solvent I
Hewlett Packard® DJ 8000s, 9000s, 10000s	Low-Solvent
Hewlett Packard H35000, H45000	788 UV pigment inks
Mimaki® JV3, JV33, JV 5	ES, SS2, SS2-1, HS
Mimaki® UVJ / UJV 160	UV Curable
Mutoh® ValueJet	Eco-Solvent
Roland® VP, SP, XC, XJ, SJ / AJ	ECO-SOL MAX / Eco-Xtreme
Océ Arizona 250 GT, 200GT	UV Inks
FujiFilm Acuity HD 2504	UV Inks
Vutek PV, QS, DS Series	UV Ink

*For further information please refer to our website www.sihlusa.com

*Performance of our adhesive products is dependent on your application.

We highly recommend that you test our product in the intended application to assure satisfactory performance.



schillers
DIGITAL PRINTER GROUP

9240 Manchester Road
St. Louis, MO 63144
dpg.schillers.com
314-968-3650 • 800-366-7244