



## **KODAK Premium** Satin Photo Paper SUV, 225gsm

# Versatile, economical, and environmentally certified

### Exceptional quality

KODAK Premium Satin Photo Paper SUV, 225gsm is a true resin-coated photo paper that provides exceptional photo-quality reproduction and meets environmental objectives with an FSC®-certification.

### Easy to handle

Engineered for low-solvent, solvent, UV-curable and Latex 300 and 500 series printers, this versatile photo paper with a satin finish is economical, easy to handle in production and may be used for a variety of applications, including photographic reproductions, posters, indoor point-of-purchase and other display applications.

### FEATURES:

- 10 mil heavyweight resin-coated photo paper
- Can be thermally laminated
- Exceptional photo quality in an economical photo paper
- FSC®-certified paper

### APPLICATIONS:

- A variety of indoor displays
- Photo reproductions
- Posters and point-of-purchase

US Size	Euro Size	Quantity	SKU
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPPS36
54" x 100'	137,1 cm x 30,5 m	1 Roll	KPPS54
61" x 100'	154,9 cm x 30,5 m	1 Roll	KPPS61

**Certified for  
HP Latex Inks**

To download media presets and check compatibility with your HP Latex Printer, please visit the HP media locator website at [hp.com/go/mediasolutionslocator](http://hp.com/go/mediasolutionslocator).



# KODAK Premium

Satin Photo Paper SUV, 225gsm

Properties	Specifications
<b>Material</b>	Resin-coated photo base
<b>Gauge</b>	10 mil
<b>Base Weight</b>	225g
<b>Gloss Level</b>	>=22
<b>Whiteness</b>	>145 CEI
<b>Environmental</b>	FSC®-certified paper
<b>Printer/Ink Compatibility</b>	Compatible with solvent, eco-solvent, UV-curable and latex inks.
<b>Software Settings</b>	Please refer to <a href="http://KODAKWFMedia.com">KODAKWFMedia.com</a> for ICC profiles for some printers.
<b>Light-fastness</b>	Inkjet ink fading time is based on the inks you use and print display environment. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
<b>Finishing/Post Processing</b>	It is always recommended that a protective laminate be applied after printing. Hand applying a laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.
<b>Optimal Service Environment</b>	72° F (21° C), 50% R.H. For end use: 0-300° F.
<b>Handling Recommendations</b>	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
<b>Ideal Storage Conditions</b>	72° F (21° C), 50% R.H. For end use: 0-300° F.
<b>Shelf Life</b>	1 year from the BMG ship date when stored in proper conditions.



The mark of responsible forestry

## KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group



9240 Manchester Road  
 St. Louis, MO 63144  
[dpg.schillers.com](http://dpg.schillers.com)  
 314-968-3650 • 800-366-7244

